

Teflon Paint Hose

Hosco Teflon Paint hose is constructed of FEP Fluoropolymer, which has excellent chemical resistance and dielectric properties, thermally superior to most other plastics, and flushes cleanly during color changing processes. It is also moisture proof, which makes it a good choice for two component paints or other moisture sensitive materials.



Heavy Wall (.063) (Larger Sizes Available)

PART NO.	OD	ID	WORKING PRESSURE
FEP - 0402	1/4"	1/8"	450 PSI (31 BAR)
FEP - 0503	5/16"	3/16"	350 PSI (24 BAR)
FEP - 0604	3/8"	1/4"	290 PSI (20 BAR)
FEP - 0705	7/16"	5/16"	250 PSI (17 BAR)
FEP - 0806	1/2"	3/8"	210 PSI (14 BAR)

Heavy Wall (1.5mm)

PART NO.	OD	ID	WORKING PRESSURE
FEPM - 9 x 6	9mm	6mm	290 PSI (20 BAR)
FEPM - 10 x 7	10mm	7mm	250 PSI (17 BAR)
FEPM - 12 x 9	12mm	9mm	210 PSI (14 BAR)

Industrial Wall (.032)

PART NO.	OD	ID	WORKING PRESSURE
FEP - 0302	3/16"	1/8"	290 PSI (20 BAR)
FEP - 0403	1/4"	3/16"	210 PSI (14 BAR)
FEP - 0504	5/16"	1/4"	165 PSI (11 BAR)

Industrial Wall (1mm)

PART NO.	OD	ID	WORKING PRESSURE
FEPM - 5 x 3	5mm	3mm	350 PSI (24 BAR)
FEPM - 6 x 4	6mm	4mm	290 PSI (20 BAR)
FEPM - 8 x 6	8mm	6mm	210 PSI (14 BAR)
FEPM - 10 x 8	10mm	8mm	165 PSI (11 BAR)

Static Wire Air Hose

Hosco Static Wire Air hose is commonly used with air atomizing spray guns where the presence of static electricity requires grounding.



HOSCO X - 1 STATIC WIRE



HOSCO X - 2 STATIC WIRE

HOSE	ID (IN.)	OD (IN.)	WORKING PRESSURE	SERVICE	APPROX WT/CFT	1/4" NPS(F)	3/8" NPS(F)
HOSCO X-1	5/16" (8mm)	5/8" (15.9mm)	200 PSI (13.6 BAR)	HD	13.8	HHC-4527	HHC-4547
HOSCO X-2	(7.5mm)	15/32" (12mm)	200 PSI (13.6 BAR)	MD	9.7	X-2-14-SS	X-2-38-SS

Construction of X-1

Tube: EDPM
 Reinforcement: 2 and 4 spiral polyester yarn
 Cover: EDPM
 Cover Color: Yellow

Construction of X-2

Tube: Urethane
 Reinforcement: Dacron Braid
 Cover: Urethane
 Cover Color: Clear